

600cc Mandatory U6SA Wing Rule

1. Top Wing

- a) Center air foil can not exceed 12 sq. ft. (1728 sq. in.) of surface area. Surface area is defined by the length x width of the flat plane of the largest projection of the center foil.
- b) Top Wing must not extend beyond outside of rear tires or behind the rear bumper.
- c) Center foil must be square or rectangular in shape with all 4 corners set to 90 degree angles.
- d) Center foil must be one piece. No split or bi-wings permitted.
- e) Maximum dimension of each side panel is 54-1/4" x 24-1/4". Only two side panels allowed. No kick-out allowed. Panels must be parallel. Maximum of 2" deep side panel, this is the protrusion of the stiffening members not including the struts (tubular or flat bar bracing).

2. Nose Wing

- a) A nose wing is optional.
- b) Center air foil can not exceed 4 sq. ft. (576 sq. in.) of surface area. Surface area is defined by the length x width of the flat plane of the largest projection of the center foil.
- c) Nose wing must not extend beyond the outside of the front tires., or beyond the front bumper.
- f) Center foil must be one piece. No split or bi-wings permitted.
- d) Maximum dimensions of each side panel is 10-1/4" x 24-1/4". Only two side panels allowed. Panels must be parallel. No kick-out allowed. Maximum of 2" deep side panel, this is the protrusion of the stiffening members not including the struts (tubular or flat bar bracing).
- a)