



## CLEAR FINISHING STAIN MIXTURE 200

### TECHNICAL DATA SHEET

#### DESCRIPTION:

Lanco Mixture 200 Clear Finishing Stain

#### USES:

Formulated for use as a finish over exterior Mixture 200 systems, unpainted concrete patios, decks, sidewalks, and driveways, concrete tennis courts and masonry walls. May be used on similar interior surfaces but only in well-ventilated areas. Do not use near open flame, pilot lights, and sparks  
Arcs. Etc. Mixture 200 is formulated to resist peeling, cracking, chipping and mildew. It's semi-gloss hard finish resists chemicals, acids, salts, detergents, chlorine, and mildew.

#### PACKAGING:

Mixture 200 is available in 5-gallon pails.

#### COVERAGE:

Coverage depends upon the porosity of the surface to be coated. Theoretical coverage of 150 square feet per gallon at 1 mil DFT on a smooth surface is obtainable. The recommended coverage is 100 to 150 square feet per gallon per coat, 2 coats recommended.

#### SURFACE PREPARATION:

Surface must be dry and clean of dust, dirt, oils, and other contaminants.

#### MIXING:

Thoroughly stir contents prior to application.

#### APPLICATION:

May be applied by brush, roller or spray. Apply only when surface temperatures are 50°F or higher. Do not apply to excessively hot surfaces because rapid drying may cause trapped vapors to bubble. Drying too rapidly may also prevent proper penetration into the substrate. Apply evenly with brush, roller or spray equipment. A 1/8" polyester nap roller is recommended. For spray applications, use a tip designed for application of gloss enamel coatings.

#### CLEAN-UP:

Roller covers should be discarded after use. Application equipment can be cleaned with Xylene or Toluol.

#### PRECAUTIONS:

**DANGER:** Causes eye burns. Vapor is harmful. May cause allergic skin reactions.

**COMBUSTIBLE:** Contains flammable solvents. Do not get in eyes, on skin or on clothing. Wear eye and skin protective

#### GENERAL DATA:

Color:	Clear
Gloss:	Semi-Gloss
Vehicle Type:	Chlorinated Rubber and Acrylic Resins
Solvent Type:	Aromatic Hydrocarbons
Solids by Volume:	24.4%
Solids by weight:	34.6%
Flash Point:	45°F
Flame Spread:	Class A Non Combustible Substrate
Coverage:	100-sq. ft./gal. At 1 Dry Mil thickness. 100-150 sq. ft./gal. /coat recommended, 2 coats
Recommended DFI	
Per coat:	1.0 to 2.0 Mil/Coat
Viscosity @ 750F:	65 KREB Units
Dry Time @ 750F:	½ hour to touch 3-4 hours to recoat
Recommended Thinner:	Xylene or Toluol

equipment when handling. Avoid breathing vapor or mist. Keep away from heat and flame. Wash thoroughly after handling. Wear appropriate, properly fitting respirator (NIOSH/MSHA APPROVED) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable levels. Follow respirator manufacturer's recommendations for use. Keep containers closed. Do not use in the presence of unprotected foodstuffs. Wear gloves when handling product.

#### NOTICE:

Reports have associated repeated and prolonged occupational over exposure to solvents with permanent

brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

#### **FIRST AID:**

In case of eye contact, flush eyes immediately with plenty of fresh water for at least 15 minutes. Call a physician. If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferable mouth to mouth, call a physician. In case of skin contact, wash immediately with soap and water. Remove contaminated clothing, launder before reuse. Discard shoes if material has penetrated inside surface.

#### **PRODUCT AVAILABILITY**

Product is available through:

Lanco Manufacturing & Distributing Inc.  
8454 N Interstate Place Suite H  
Portland, Oregon 97217

Toll Free: 1-877-706-4400  
Phone: (503) 285-8200  
Fax: (503) 285-8245  
E-mail: [lancoproducts@yahoo.com](mailto:lancoproducts@yahoo.com)  
Web Site: [www.lanco-mfg.com](http://www.lanco-mfg.com)

#### **TECHNICAL/SPECIFICATION SERVICES**

Additional product data, complete technical support and product specifications are all available through Lanco Manufacturing & Distribution Inc.; or their local representatives.

Every reasonable precaution and effort has been taken in the manufacturing of all Lanco products to comply with the published product data. Actual product performance may vary slightly due to environmental influences and/or conditions.

#### **LIMITED WARRANTY**

Lanco Manufacturing & Distributing warrants its product to be of good quality and will replace any product proved defective. Satisfactory results depend not only upon quality products but also upon many factors beyond our control. Therefore, except for such replacement, **LANCO MANUFACTURING & DISTRIBUTING MAKES NO WARRANTY OR GUARANTEE, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS LANCO MANUFACTURING & DISTRIBUTING INC. PRODUCTS**, and Lanco Manufacturing & Distributing Inc. shall have no other liability with respect thereto, including without limitation, liability for incidental or consequential damages. Any

claim regarding product defect must be received in writing within one hundred and eighty (180) days from the date of shipment. No claim will be considered without such written notice or after the specified time interval. The user shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith.

---

Toll Free: 1-877-706-4400 / Phone: (503) 285-8200 / Fax: (503) 285-8245  
8454 N Interstate Place Suite H, Portland, Oregon 97217  
Check us out on the web: [www.lanco-mfg.com](http://www.lanco-mfg.com)